



# Setting the standard in Surface-mounted LED Downlight

## GreenSpace Surface-mounted

Philips GreenSpace Surface-mounted LED Downlight delivers a superior LED alternative that's up to 66% more energy efficient than the conventional downlight retrofits. Blending seamlessly into its environment, GreenSpace Surface-mounted LED Downlight mimics the form of conventional recessed downlights minus the associated high energy and maintenance costs. Philips GreenSpace Surface-mounted LED Downlight is also ideal for all commercial lighting applications as well as public indoor space where there is limited space in the ceiling.

### Benefits

- Lumen output: Different lumens in different sizes and mounting heights with options of 1000lm, 2000lm, 3800lm & 6600lm.
- Superior light performance: Colours rendered accurately (CRI>80) and high system efficacy (100lm/w)
- Varieties: IP20, IP65 version with choice of different lumen output, and option of black housing through tailor-made
- Long lifetime: 50,000 hour lifetime ensures more savings in the long run

### Features

- System efficacy: 100lm/W, energy saving up to 66% vs conventional downlights
- Reliable performance: Lifetime 50,000 hours (L70B50@Ta25°C)
- Excellent light quality - CRI>=80 @3000K, 4000K and 6500K
- Integral lightweight design - Installation cost is significantly reduced

## GreenSpace Surface-mounted

### Application

- Shopping mall
- Station concourse
- Canopy
- Airport public area
- Stadium public area

### Versions



SM291C/SM293C

# GreenSpace Surface-mounted

-	
Driver failure rate at 5,000 hours	1.00 %
<b>Application Conditions</b>	
Ambient temperature range	-20 to +40 °C
Suitable for random switching	No
<b>Approval and Application</b>	
Mech. impact protection code	IK02
<b>Controls and Dimming</b>	
Dimmable	No
<b>Operating and Electrical</b>	
Input Voltage	220 to 240 V
<b>General Information</b>	
Beam angle of light source	- °
CE mark	CE mark
Protection class IEC	Safety class I (I)
Optical cover/lens type	Reflector
Driver included	Yes
ENEC mark	-
Flammability mark	NO
Glow-wire test	750/5
Light source replaceable	No
Number of gear units	1 unit
Optic type	C
<b>Initial Performance (IEC Compliant)</b>	
Init. Colour rendering index	>80
Luminous flux tolerance	+/-10%
<b>Mechanical and Housing</b>	
Colour	White
<b>Over Time Performance (IEC Compliant)</b>	
Median useful life L80B50	40000 h
Median useful life L90B50	20000 h

## Approval and Application

Order Code	Full Product Name	Ingress protection code
911401847199	SM291C LED10/830 PSU WH GM	IP20
911401847299	SM291C LED10/840 PSU WH GM	IP20
911401847499	SM293C LED20/830 PSU WH GM	IP20
911401847599	SM293C LED20/840 PSU WH GM	IP20
911401847799	SM295C LED70/840 PSU WP WH GM	IP65
911401848099	SM295C LED70/865 PSU WP WH GM	IP65
911401848299	SM294C LED40/865 PSU WP WH GM	IP65
911401848699	SM294C LED40/840 PSU WH GM	IP20
911401848899	SM295C LED70/840 PSU WH GM	IP20

## Initial Performance (IEC Compliant) (1/2)

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Colour Temperature	Initial LED luminaire efficacy	Initial luminous flux
911401847199	SM291C LED10/830 PSU WH GM	(0.44, 0.40) SDCM <5	3000 K	100 lm/W	1000 lm
911401847299	SM291C LED10/840 PSU WH GM	(0.38, 0.38) SDCM <5	4000 K	100 lm/W	1000 lm
911401847499	SM293C LED20/830 PSU WH GM	(0.44, 0.40) SDCM <5	3000 K	105 lm/W	2000 lm
911401847599	SM293C LED20/840 PSU WH GM	(0.38, 0.38) SDCM <5	4000 K	105 lm/W	2000 lm
911401847799	SM295C LED70/840	(0.38, 0.38) SDCM <5	4000 K	100 lm/W	6600 lm

## GreenSpace Surface-mounted

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Colour Temperature	Initial LED luminaire efficacy	Initial luminous flux
	PSU WP WH GM				
911401848099	SM295C LED70/865 PSU WP WH GM	(0.31, 0.32)	6500 K	100 lm/W	6600 lm
	SM295C LED70/865 PSU WP WH GM	SDCM <5			
911401848299	SM294C LED40/865 PSU WP WH GM	(0.31, 0.32)	6500 K	105 lm/W	3800 lm
	SM294C LED40/865 PSU WP WH GM	SDCM <5			

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Colour Temperature	Initial LED luminaire efficacy	Initial luminous flux
911401848699	SM294C LED40/840 PSU WH GM	(0.38, 0.38)	4000 K	100 lm/W	3800 lm
	SM294C LED40/840 PSU WH GM	SDCM <5			
911401848899	SM295C LED70/840 PSU WH GM	(0.38, 0.38)	4000 K	100 lm/W	6600 lm
	SM295C LED70/840 PSU WH GM	SDCM <5			

### Initial Performance (IEC Compliant) (2/2)

Order Code	Full Product Name	Initial input power
911401847199	SM291C LED10/830 PSU WH GM	10 W
911401847299	SM291C LED10/840 PSU WH GM	10 W
911401847499	SM293C LED20/830 PSU WH GM	19 W
911401847599	SM293C LED20/840 PSU WH GM	19 W
911401847799	SM295C LED70/840 PSU WP WH GM	66 W

Order Code	Full Product Name	Initial input power
911401848099	SM295C LED70/865 PSU WP WH GM	66 W
911401848299	SM294C LED40/865 PSU WP WH GM	36 W
911401848699	SM294C LED40/840 PSU WH GM	38 W
911401848899	SM295C LED70/840 PSU WH GM	66 W

