

**PHILIPS**

Lighting



# GreenPerform Highbay Rectangular

## BY570P LED200/CW PSU HRO GM

Transparent dome

As the first IP65 rectangular LED highbay under the GreenPerform family, the GreenPerform Highbay Rectangular with dedicated optical design, leading system efficiency and compact dimensions, is the optimised solution for warehousing and logistics-related applications.

### Product data

#### General Information

Lamp colour code	865 cool daylight
Optical cover/lens type	TSDM [ Transparent dome]
Control interface	-
Protection class IEC	Safety class I (I)
CE mark	CE mark
Number of products on MCB (16 A type B)	6
Light source engine type	LED

#### Operating and Electrical

Input Voltage	220 to 240 V
Input frequency	50 or 60 Hz
Power factor (min.)	0.95

#### Controls and Dimming

Dimmable	No
----------	----

#### Mechanical and Housing

Housing material	Aluminum die-cast
Optical cover/lens material	Polycarbonate
Optical cover/lens finish	Clear
Overall length	27 mm
Overall width	11 mm
Overall height	34 mm
Colour	Grey

#### Approval and Application

Ingress protection code	IP65 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [ 1 J]

#### Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	20000 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	139 lm/W
Lamp colour temperature	6500 K

## GreenPerform Highbay Rectangular

Colour Rendering Index	>80
Initial input power	144 W
Power consumption tolerance	+/-10%


### Application Conditions

Ambient temperature range	-30 to +50 °C
---------------------------	---------------


### Product Data

Full product code	911401591761
-------------------	--------------

Order product name	BY570P LED200/CW PSU HRO GM
Order code	911401591761
SAP numerator – quantity per pack	1
Numerator – packs per outer box	2
SAP material	911401591761
SAP net weight (piece)	3.599 kg



## Dimensional drawing



High-bay/ low-bay LED

