



UniStrip G4

BCP384 36LED 30K 220V A2 L100 DMX D2

3000 K

UniStrip G4 is a surface-mounted, exterior-rated LED luminaire that is designed for façade and outdoor architectural lighting applications. One family that fits all your needs, wall washing, grazing and also linear flood lighting. The robust mechanical and unique optical designs make it ideal for illuminating buildings facades, bridges, overpasses and any application that requires a linear lighting solution. Available in white, monochromatic colours, RGB, RGBW and tunable white and DMX control option available with up to 8 pixels (8IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

Warnings and Safety

- For outdoor use only

Product data

General Information		Line Frequency	
Driver included	Yes	Line Frequency	50 to 60 Hz
Lighting Technology	LED	Input Frequency	50 to 60 Hz
Light Technical		Power Consumption	80 W
Luminous Flux	4,195 lumen	Inrush current	60 A
Correlated Color Temperature (Nom)	3000 K	Power Factor (Fraction)	0.9
Luminous Efficacy (rated) (Nom)	52 lm/W	Connection	Flying leads/wires and 2 Push-in connector 4-pole
Color rendering index (CRI)	80	Cable	Cable 0.3 m without plug 3-pole + 2 Cables 0.3 m with connector 4-pole
Light source color	Warm white	Temperature	
Optical cover/lens type	Tempered glass	Ambient temperature range	-40 to +50 °C
Operating and Electrical			
Input Voltage	220 to 240 V		

UniStrip G4

Controls and Dimming

Dimmable	Yes
Control interface	Dynamix DMX

Mechanical and Housing

Housing Material	Aluminum extruded
Optical cover/lens material	Polymethyl methacrylate
Housing Color	Dark gray
Effective projected area	0.085 m ²

Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]
Protection class IEC	Safety class I
Flammability mark	For mounting on normally flammable surfaces
CE mark	CE mark

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	SDCM = 4
Power consumption tolerance	+/-10%

Product Data

Full product code	871951492210599
Order product name	BCP384 36LED 30K 220V A2 L100 DMX D2
Order code	911401736643
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material number (12NC)	911401736643
Full product name	BCP384 36LED 30K 220V A2 L100 DMX D2
EAN/UPC - Case	8719514922105



Dimensional drawing

