



# UniStrip G4

## BCP386 30LED RGB 24V 30 L50 DMX

UniStrip G4 is a surface-mounted, exterior-rated LED luminaire that is designed for façade and outdoor architectural lighting applications. One family that fits all your needs, wall washing, grazing and also linear flood lighting. The robust mechanical and unique optical designs make it ideal for illuminating buildings facades, bridges, overpasses and any application that requires a linear lighting solution. Available in white, monochromatic colours, RGB, RGBW and tunable white and DMX control option available with up to 8 pixels (8IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

### Warnings and Safety

- For outdoor use only

### Product data

General Information		Line Frequency	
Driver included	No	Line Frequency	- Hz
Lighting Technology	LED	Input Frequency	- Hz
Light Technical		Power Consumption	7.5 W
Luminous Flux	240 lumen	Power Factor (Fraction)	0.9
Correlated Color Temperature (Nom)	-	Connection	2 Push-in connector 5-pole
Luminous Efficacy (rated) (Nom)	32 lm/W	Cable	2 cables 0.15m with connectors 5-pole
Color rendering index (CRI)	-	Temperature	
Light source color	Red, green and blue	Ambient temperature range	-40 to +50 °C
Optical cover/lens type	Clear glass	Controls and Dimming	
Operating and Electrical		Dimmable	Yes
Input Voltage	24 DC V	Control interface	Dynamic DMX

# UniStrip G4

## Mechanical and Housing

Housing Material	Aluminum extruded
Optical cover/lens material	Polymethyl methacrylate
Housing Color	Dark gray
Overall length	500 mm
Overall width	25.4 mm
Overall height	71.6 mm
Dimensions (Height x Width x Depth)	72 x 25 x 500 mm

## Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]
Protection class IEC	Safety class III
CE mark	CE mark

## Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
-------------------------	--------

Power consumption tolerance	+/-10%
-----------------------------	--------

## Product Data

Full product code	871951451403499
Order product name	BCP386 30LED RGB 24V 30 L50 DMX
Order code	911401780382
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material number (12NC)	911401780382
Full product name	BCP386 30LED RGB 24V 30 L50 DMX
EAN/UPC - Case	8719514514034



## Dimensional drawing

