



UniStrip G4

BCP386 60LED 27K 24V 60 L100

2700 K

UniStrip G4 is a surface-mounted, exterior-rated LED luminaire that is designed for façade and outdoor architectural lighting applications. One family that fits all your needs, wall washing, grazing and also linear flood lighting. The robust mechanical and unique optical designs make it ideal for illuminating buildings facades, bridges, overpasses and any application that requires a linear lighting solution. Available in white, monochromatic colours, RGB, RGBW and tunable white and DMX control option available with up to 8 pixels (8IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

Warnings and Safety

- For outdoor use only

Product data

General Information		Line Frequency	
Driver included	No	Line Frequency	- Hz
Lighting Technology	LED	Input Frequency	- Hz
Light Technical		Power Consumption	15 W
Luminous Flux	985 lumen	Power Factor (Fraction)	0.9
Correlated Color Temperature (Nom)	2700 K	Connection	2 Push-in connector 2-pole
Luminous Efficacy (rated) (Nom)	66 lm/W	Cable	2 cables 0.15m with connectors 2-pole
Color rendering index (CRI)	80	Temperature	
Light source color	Warm white	Ambient temperature range	-40 to +50 °C
Optical cover/lens type	Clear glass	Controls and Dimming	
Operating and Electrical		Dimmable	No
Input Voltage	24 DC V	Control interface	-

UniStrip G4

Mechanical and Housing

Housing Material	Aluminum extruded
Optical cover/lens material	Polymethyl methacrylate
Housing Color	Dark gray
Overall length	1,000 mm
Overall width	25.4 mm
Overall height	71.6 mm
Dimensions (Height x Width x Depth)	72 x 25 x 1000 mm

Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]
Protection class IEC	Safety class III
CE mark	CE mark

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
-------------------------	--------

Power consumption tolerance	+/-10%
-----------------------------	--------

Product Data

Full product code	871951451413399
Order product name	BCP386 60LED 27K 24V 60 L100
Order code	911401780482
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material number (12NC)	911401780482
Full product name	BCP386 60LED 27K 24V 60 L100
EAN/UPC - Case	8719514514133



Dimensional drawing

